

Date: _____

Type: _____

Project: _____

AURORA SURFACE MOUNT

Introducing AURORA, our stocky surface luminaire. Created to illuminate interior spaces such as corridors, hallways, unique rooms, and mixed-use areas. Luminaire housing features an opal polycarbonate lens that is flat on the circular face and enveloped by a cast aluminum frame highlighting a glow band at the side. Direct down and side light is our standard. Faces can be closed for direct down light or side light only.

Construction: Fixture is made from solid cast aluminum frame equipped with regressed stainless-steel allen screws for its standard design. Weather-proof silicon gasket seal is used along with stainless-steel external hardware for all-weather protection and corrosion resistance.

Mounting: Fixture is suitable to mount over a standard J-box. This fixture can be ceiling mounted or wall mounted.

Lens: Illuminate your space with opal polycarbonate lens.

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: 0-10V 10% dimming, wet location, mesh around lens


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



AURORA:



FRONT VIEW



BOTTOM VIEW



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Size	Lamping	Electrical	Color Temperature	Mounting	Light Pattern	Lens	Options	Finish
AURORA	14"	20W LED	UNV	3000K	CM	DS	OPL	DM	BL
			347V	3500K	WM	D		PERF	BZ
			480V	4000K		S		WL	WH
				5000K					SG
			custom wattage and size available						CC

Notes:

- 3000K – 141 lm/w
- 3500K – 144 lm/w
- 4000K – 147 lm/w
- 5000K – 149 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- CM – Ceiling mount
- WM – Wall mount
- DS – Down and side light (std)
- D – Down light
- S – Side light
- OPL – Opal polycarbonate lens
- DM – 0-10V 10% dimming
- WL – Wet location
- PERF – Perforated mesh around lens
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)