

Date: _____

Type: _____

Project: _____

BORNA POST TOP

BORNA has a classic design with modern LED technology. This octagonal luminaire exudes a gothic style constructed using heavy wall aluminum casting. Explore the many mounting options. All its external hardware is stainless-steel. We can customize for lower wattages.

Construction: Fixture housing is constructed heavy wall aluminum castings with weatherproof silicone gasket sealing for all weather protection and dependable durability. External hardware is stainless-steel for corrosion resistance.

Mounting: slips over 3" or 4" pole, wall mounted from straight arm, chain hung from ceiling

Lens: opal lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type V

Driver: 60Hz, 120-277V / 347V/ 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: 0-10v 10% dimming, button photocell, programmable color changing LEDs


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



BORNA:



TOP VIEW



FRONT VIEW

FIXTURE	DIM-A	DIM-B
BORNA-18	18"	9 3/4"
BORNA-22	22"	11 3/4"
BORNA-29	29"	15 1/4"

Note: Available in wall mount and chain hung options.



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
BORNA-18	32W	3000K	UNV	PT3	OPL	TY5	CUSTOM	BL
BORNA-22	48W	3500K	347V	PT4			DM	BZ
BORNA-29	69W	4000K	480V	PT5			PC	WH
		5000K					RGBW	SG
custom wattage available								CC

Notes:

- 3000K – 156 lm/w
- 3500K – 159 lm/w
- 4000K – 164 lm/w
- 5000K – 166 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- PT3- Post top on 3" od tenon/pole
- PT4- Post top on 3" od tenon/pole
- PT5- Post top on 3" od tenon/pole
- OPL – Opal lens (std)
- TY5 – Type V light distribution
- CUSTOM – custom pole configuration, contact factory
- DM – 0-10v 10% dimming
- PC – Voltage specific button photocell
- RGBW – Programmable color changing LEDs
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (confirm RAL No. prior to production)

*Does not apply to RGBW