

Date: _____

Type: _____

Project: _____

COM WALL RECESSED

COM is a recessed wall luminaire made with cast aluminum face plate and fabricated aluminum back box with standard forward throwing illumination. It comes with lens that is silicone sealed for bug and weather protection. All external hardware is stainless-steel.

Construction: Fixture housing is constructed from aluminum for durability with weatherproof silicon gasket seal for all weather protection. Its back box is continuously welded. External hardware is stainless-steel for corrosion resistance.

Mounting: Fixture is suitable for recessed mounting in drywall or concrete.

Lens: opal, frosted

Light distribution: forward throw

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, wet location




Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location

Warranty: 5-year limited warranty



COM:



BACK BOX SIZE: 7 1/4" x 4 1/4" x 2 1/4"



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
COM	6W	3000K	UNV	R	OPL	FT	TP	BL
		3500K	347V	RTC	FG		TS	BZ
		4000K	480V				WL	WH
custom wattage available		5000K						SG
								CC

Notes:

- 3000K – 191 lm/w
- 3500K – 198 lm/w
- 4000K – 204 lm/w
- 5000K – 204 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- R – Recessed in dry wall
- RTC – Recessed in concrete
- OPL – Opal polycarbonate lens
- FG – Frosted lens
- FT – Forward throw
- TP – Tamperproof hardware
- TS – Tamperproof bits
- WL – Wet location
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)