

Date: _____

Type: _____

Project: _____

CORVUS WALL RECESSED

CORVUS is a compact wall luminaire constructed with cast aluminum housing with silicone sealed lens. All external hardware is stainless-steel.

Construction: Fixture housing is constructed from cast aluminum for durability with weatherproof silicon gasket seal for all weather protection. External hardware is stainless-steel for corrosion resistance.

Mounting: Fixture is suitable to mount over standard 2" x 4" recessed J-box.

Lens: opal

Light distribution: forward throw

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Driver: 60Hz, 120-277V / 347V/ 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



CORVUS:



SIDE VIEW



FRONT VIEW



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
CORVUS	3W	3000K	UNV	WM	OPL	FT	TP	BL
		3500K	347V				TS	BZ
		4000K	480V					WH
		custom wattage available	5000K					SG
					CC			

Notes:

- 3000K – 191 lm/w
- 3500K – 198 lm/w
- 4000K – 204 lm/w
- 5000K – 204 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- WM – Wall mount (over 2"x4" standard J-box)
- OPL – Opal polycarbonate lens
- FT – Forward throw
- TP – Tamperproof hardware
- TS – Tamperproof bits
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)