

Date: _____

Type: _____

Project: _____

DGR-PT POST TOP

Elevate your outdoor space with our sleek, modern DGR lantern series. Its elegant black frame and versatile lighting make it perfect for gardens, pathways, or driveways, adding a touch of sophistication and charm to your area.

Construction: Fixture housing is constructed from aluminum for durability. Weather-proof silicone gasket seal for all weather protection. Stainless steel external hardware for corrosion resistance.

Mounting: post top slips over 3" or 4" pole

Lens: Standard opal lens emit a comforting glow.

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type V

Driver: 60Hz, 120-277V / 347V/ 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: Button photocell, 0-10V 10% dimming


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



DGR-PT:



FRONT VIEW



TOP VIEW



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
DGR-PT	60W	3000K	UNV	PT3	OAL	TY5	DM	BL
		3500K	HLV	PT4			PC	BZ
		4000K						WH
		5000K						SG
								CC

Notes:

- 3000K – 191 lm/w
- 3500K – 198 lm/w
- 4000K – 204 lm/w
- 5000K – 204 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- PT3 – Post top slips over 3" pole
- PT4 – Post top slips over 4" pole
- OAL – Opal lens (std)
- TY5 – Type V light distribution (std)
- PC – voltage specific button photocell
- DM- 0-10V 10% dimming
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)