

Date: _____

Type: _____

Project: _____

GAR-C LIGHT COLUMN

Elevate your space with this contemporary light column. Designed not only for robust security but also to enhance aesthetic appeal. Its elegant curved top add a touch of sophistication, making it an ideal choice for those looking to combine functionality with style. Durable and easy to install, this column is perfect for delineating spaces while complementing any modern architectural design.

Construction: Discover the perfect blend of durability and elegance with our extruded aluminum light column. Its silicone-sealed lens gasket ensure superior protection and longevity. Ideal for modern spaces, this column not only enhances security but also adds a sleek, sophisticated touch to any environment.

Mounting: The fixture housing attaches securely to the anchoring plate using four flush-mounted anchor bolts. The package includes the necessary anchors (A), bolts (B), and a template (T).

Lens: Choose standard clear lens for optimal visibility or lexan lens for enhanced vandal resistance, ensuring clarity and durability.

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type II, Type III, Type IV

Driver: 60Hz, 120-277V / 347-480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, step dimming, motion sensor, button photocell (voltage specific), ground fault receptacle, base cover, emergency driver, base cover


Finish: black, white, silver grey, bronze, custom color available upon request, hydro-dipped finish

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



GAR-C:



Anchoring Details:



Anchorbolt Size: 3/4" X 18" X 3-3/4"

- Hot dipped Galvanized anchor bolts
- Galvanized steel hex nuts
- Galvanized steel flat washers



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Height	Light Engine	Electrical	Color Temp	Mounting	Lens	Light Pattern	Options	Finish
GAR-C	12FT	42W	UNV	3000K	ABT	CPL	TY2	TP	BL
			347V	3500K		PR	TY3	TS	BZ
			480V	4000K		LE	TY4	SD	WH
				5000K				MS	SG
								PC	CC
								GFR	H-DIP
								BC	
custom wattage and size available									

Notes:

- 3000K – 152 Source lm/w
- 3500K – 157 Source lm/w
- 4000K – 160 Source lm/w
- 5000K – 160 Source lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 Volt
- 480V – 480 Volt
- ABT – Anchors, bolts, template
- CPL – Clear lens (std)
- PR – Prismatic lens (K12)
- LE – Lexan lens (vandal resistant)
- TY2 – Type II light distribution
- TY3 – Type III light distribution
- TY4 – Type IV light distribution
- TP – Tamperproof hardware
- TS – Tamperproof bits
- SD – Step dimming
- MS – Motion sensor
- PC – Button photocell, voltage specific
- GFR – Ground fault receptacle
- BC – Base cover
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver grey
- CC – Custom color (Confirm RAL No. prior to production)
- H-DIP – Hydro-dipped finish (contact factory for pattern design options)