

Date: _____

Type: _____

Project: _____

GRANT BOLLARD

Presenting the Grant Bollard! With a slanting top and a modern 3-strip face cut-out, this bollard seamlessly blend into your outdoor landscape during the day. By night, its specialized optics casts a subtle illumination, jazzing up walkways with futuristic elegance.

Construction: Discover the innovative charm of our 39-inch standard bollard crafted from durable aluminum structured with 60-degree slant at the top. Its precise 3-vertical cut-out strips give a captivating visual appeal. Whether lining pathways or accentuating garden features, this bollard seals the deal.

Mounting: The fixture attaches securely to the ground and anchoring plate using four flush-mounted anchor bolts. The package includes the necessary anchors (A), bolts (B), and a template (T).

Lens: Our standard opal lens gently diffuses light creating a soft inviting ambiance.

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: The soft glow on both sides gives a soothing appeal.

Driver: 60Hz, 120-277V / 347V/ 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, 0-10v dimming, ground fault receptacle, button photocell (voltage specific)


Finish: black, white, silver grey, bronze, custom color available upon request, hydro-dipped

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



GRANT:




FRONT VIEW



SIDE VIEW

Anchoring Details:



1.5" BOLT PROJECTION

BOLT SIZE: 1/2" X 12" X 1-3/8"

- Hot dipped Galvanized anchor bolts
- Galvanized steel hex nuts
- Galvanized steel flat washers



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Height	Light Engine	Electrical	Color Temperature	Mounting	Lens	Light Pattern	Options	Finish
GRANT	39"	30W	UNV	3000K	ABT	OPL	SOFT	TP	BL
			347V	3500K				TS	BZ
			480V	4000K				DM	WH
				5000K				GFR	SG
								PC	CC
Custom wattage and size available									H-DIP

Notes:

- 3000K – 141 lm/w
- 3500K – 144 lm/w
- 4000K – 147 lm/w
- 5000K – 149 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- ABT – Anchor, bolts, & template
- OPL – Opal lens (std)
- SOFT – Soft glow on both sides
- TP – Tamperproof hardware
- TS – Tamperproof bits
- DM – 0-10V 10% dimming
- GFR – Ground fault receptacle
- PC – Button photocell (voltage specific)
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver grey
- CC – Custom color (confirm RAL No. prior to production)
- H-DIP – Hydro-dipped finish (contact factory for pattern design options)