

Date: _____

Type: _____

Project: _____

KING POST TOP

Introducing our colonial post top with rustic design. KING is made from cast aluminum with design featuring a spiked cage encasing the reflective cone. The spikes are set at the upper hood and bottom portion of the luminaire walled by clear lens. The finial at the top cover is customizable. Its over-all design gives a traditional appeal with enhanced illumination on all sides. Its slip fitter at the base is made of cast aluminum. The lens is silicone sealed for full weather protection. All external hardware is stainless-steel. We can customize for lower wattages. Contact factory for other pole & base accessories and other mounting options.

Construction: Fixture housing is constructed from cast aluminum for durability with weatherproof silicone gasket sealing for all weather protection. External hardware is stainless-steel for corrosion resistance.

Mounting: post top slips over 3" or 4" pole, pier mount, chain hung

Lens: clear lens, prismatic lens, fisher lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type V

Driver: 60Hz, 120-277V / 347V/ 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, button photocell, house side shield, decorative glass chimney, internal louvers


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



KING:




FRONT VIEW



TOP VIEW


OPTIONS:



REFLECTIVE CONE



LOUVERS



GLASS CHIMNEY

NOTE: Available in pier mount version

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
KING	60W	3000K	UNV	PT3	CL	TY5	PC	BL
		3500K	347V	PT4	PG		TCO	BZ
		4000K	480V	PT5	FSR		CHI-CL	WH
		5000K					CHI-FR	SG
							ILO	CC
	custom wattage available;						FINIAL	

Notes:

- 3000K – 152 lm/w
- 3500K – 157 lm/w
- 4000K – 160 lm/w
- 5000K – 160 lm/w
- UNV – Universal voltage (120-277V)
- 347V –347 volts
- 480V –480 volts
- PT3 – Post top slips over 3" pole
- PT4 – Post top slips over 4" pole
- PT5 – Post top slips over 5" pole
- CL – Clear lens (std)
- PG – Prismatic lens (K12)
- FSR – Fisher lens
- TY5 – Type V light distribution (std), with reflective cone
- PC – voltage specific button photocell
- TCO –trespass cut-off shield
- CHI-CL – Clear decorative glass chimney
- CHI-FR – Frosted decorative glass chimney
- ILO – Internal louvers with Type V light distribution
- FINIAL – Custom finial, contact factory for finial design options
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (confirm RAL No. prior to production)