



CUSTOM ARCHITECTURAL LIGHTING

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Toll free: 1 877 765 3722

Fax: 905 457 1115

soleracorp.com

Date: _____

Type: _____

Project: _____

NEMO-BLD BOLLARD

Modern & simplistic with slanting design on the shaft. Body has smooth and sharp corners.

Construction: Fixture housing constructed from 6061 aluminum alloy. Weatherproof silicon gasket seal for all weather protection. Stainless steel external hardware for corrosion resistance.

Mounting: The fixture attaches securely to the ground and anchoring plate using four flush-mounted anchor bolts. The package includes the necessary anchors (A), bolts (B), and a template (T).

Lens: Opal lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type V

Driver: 60Hz, 120-277V / 347V/480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature ranging between -40°C to 55°C.

Options: 0-10V dimming, 10KV/20KV surge protector, ground fault receptacle, tamperproof hardware, tamperproof bits, color changing LED, custom height (contact Factory)


Finish: black, white, silver gray, bronze, custom color available upon request, hydro-dipped finish

Listing: complies with CSA & UL standards; approved for indoor and outdoor location


Warranty: 5-year limited warranty



NEMO-BLD:





FRONT



TOP

ANCHORING DETAILS:





CUSTOM ARCHITECTURAL LIGHTING • 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Toll free: 1 877 765 3722

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Height (inches)	Light Engine	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options		Finish
NEMO-BLD	36	25 W (max)	3000K 3500K 4000K 5000K	UNV 347V 480V	ABT	OPL	TY5	TP TS DM GFR	SP10 SP20 RGBW	BL BZ WH SG
Contact Factory for custom height										CC H-DIP

Notes:

- 3000K – 156 Source lm/w*
- 3500K – 159 Source lm/w*
- 4000K – 164 Source lm/w*
- 5000K – 166 Source lm/w*
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- ABT – Anchors, bolts, template
- OPL – Opal lens
- TY5 – Type V light distribution
- TP – Tamperproof hardware
- TS – Tamperproof bits
- DM – 0-10V 10% dimming
- GFR – Ground fault receptacle
- SP10 – Surge protector up to 10 KV
- SP20 – Surge protector up to 20 KV
- RGBW – color changing programmable LED
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)
- H-DIP – Hydro-dipped finish (contact factory for pattern design options)

*Does not apply to RGBW