

Date: _____

Type: _____

Project: _____

GLOBE POST TOP

The Outdoor Globe Series uses architectural grade seamless acrylic sphere. The standard is opal acrylic globe. See the pendant version under Interior Luminaires and the wall mount version under Exterior Luminaires.

Construction: Fixture housing constructed from aluminum alloy. Weatherproof silicon gasket seal for all weather protection. Stainless steel external hardware for corrosion resistance.

Mounting: Fixture is suitable to mount over pole or tenon.

Lens: opal globe, clear globe

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: encompassing glow

Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C

Options: internal louvers for clear globe, 0-10v 10% dimming, tamperproof hardware, tamperproof bits, button photocell


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location

Warranty: 5-year limited warranty



GLOBE-PT :



Note: Available in pendant and wall mount versions.



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Size	Lamping	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
GLOBE	12	12W	3000K	UNV	PT3	OAL	EG	ILO	BL
	14	18W	3500K	347V	PT4	CPL		DM	BZ
	16	30W	4000K	480V				TP	WH
	18	48W	5000K					TS	SG
	20	60W							CC
	22	72W							

Notes:

- 3000K – 141 lm/w
- 3500K – 144 lm/w
- 4000K – 147 lm/w
- 5000K – 149 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- PT3 – Post top slips over 3" pole
- PT4 – Post top slips over 4" pole
- OAL – Opal acrylic lens
- CPL – Clear acrylic lens
- ILO – Internal louvers, for CPL only
- DM – 0-10v 10% dimming
- TP – Tamperproof hardware
- TS – Tamperproof bits
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (confirm RAL No. prior to production)
- PLY- Polycarbonate