

Date: _____

Type: _____

Project: _____

STEPLIGHTS WALL

Our STEPLIGHTS are made of cast aluminum face plate with fabricated aluminum back box. The lens is silicone sealed to doorframe for weather protection. All external hardware is stainless-steel.

Construction: Fixture housing is constructed of cast aluminum face plate with fabricated aluminum back box with weatherproof silicon gasket seal for all weather protection. External hardware is stainless-steel for corrosion resistance.

Mounting: Fixture is suitable to mount recessed in dry wall or concrete.

Lens: opal or frosted

Light distribution: front light

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, double face, remote emergency battery


Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty




STEPLIGHTS:



TOP VIEW



FRONT VIEW



SIDE VIEW

FACE DESIGNS:



SFSL



SGSL



SLSL



SBSL



CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--

Name	Light Engine (maximum)	Color Temperature	Electrical	Mounting	Lens	Light Pattern	Options	Finish
SCSL	12W	3000K	UNV	R	OAL	F	TP	BL
SFSL		3500K	347V	RTC	FG		TS	BZ
SGSL		4000K	480V				DF	WH
SBSL		5000K					EM-RB	SG
SLSL								CC
custom wattage available								

Notes:

- 3000K – 191 lm/w
- 3500K – 198 lm/w
- 4000K – 204 lm/w
- 5000K – 204 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- R – Recessed in dry wall
- RTC – Recessed in concrete
- OAL – Opal acrylic lens (std)
- FG – Frosted glass lens
- TP – Tamperproof hardware
- TS – Tamperproof bits
- DF – Double face
- EM-RB – Remote emergency battery
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)