

Date: _____

Type: _____

Project: _____

TIC-TAC-TOE WALL MOUNT

Our square wall luminaire with square cut aluminum overlay on opal lens. TIC-TAC-TOE gives up, down, and front illumination. Choose from different lens colors for the front face. This is an attractive and youthful choice for lighting corridors or halls of hotels, schools, or recreation centers. All external hardware is stainless steel.

Construction: Fixture is made from aluminum extrusion with weather-proof silicon gasket seal and stainless-steel external hardware for all-weather protection and corrosion resistance. We have two sizes available at 12" or 16" square. The depth is standard at 4".

Mounting: Fixture is suitable to mount over a standard J-box.

Lens: Opal, red, blue, green, yellow lens

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: up, down, front glow


Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating Temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, 0-10v 10% dimming, wet location



Finish: black, white, silver grey, bronze, custom color available upon request

Listing: complies with CSA & UL standards; label for indoor location

Warranty: 5-year limited warranty



TIC-TAC-TOE:



PRODUCT	DIM "A"	DIM "B"	DIM "C"
TTT-12	12"	12"	4"
TTT-16	16"	16"	4"

--	--	--	--	--	--	--	--	--	--

Name	Size	Light Engine	Color Temp	Electrical	Mounting	Lens	Light Pattern	Options	Finish
TIC-TAC-TOE	12" (18 W Max)	18W LED	3000K	UNV	WM	OAL	UDF	TP	BL
	16" (36W Max)	36W LED	3500K	347V		RED	UF	TS	BZ
			4000K	480V		BLUE	DF	DM	WH
			5000K			GREEN			SG
						YELLOW			CC

Notes:

- 3000K – 191 lm/w
- 3500K – 198 lm/w
- 4000K – 204 lm/w
- 5000K – 204 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- WM – Wall mount
- OAL – Opal lens
- RED – Red lens for front
- BLUE – Blue lens for front
- GREEN – Green lens for front
- YELLOW – Yellow lens for front
- UDF – Up and down light with front glow (std)
- UF – Up light only with front glow
- DF – Down light only with front glow
- TP – Tamperproof hardware
- TS – Tamperproof bits
- DM – 0-10v 10% dimming
- WL – Wet location
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver gray
- CC – Custom color (Confirm RAL No. prior to production)