

Date: _____

Type: _____

Project: _____

UNB BOLLARD

Introducing the UNB bollard, a sleek and stylish lighting solution that sits low to the ground, seamlessly blending into any landscape. The modern design adds a touch of elegance to outdoor spaces. Elevate your space with this sophisticated and efficient lighting fixture, designed to provide a long-lasting performance. Make a statement both day and night with the UNB bollard!

Construction: Expertly crafted from high-quality fabricated aluminum for a sleek and durable finish. The top assembly features a stylish louvered design, adding a modern touch to any setting. All external hardware is made from premium stainless steel, ensuring long-lasting performance and resistance to the elements.

Mounting: The fixture housing attaches securely to the anchoring plate using three flush-mounted anchor bolts. The package includes the necessary anchors (A), bolts (B), and a template (T).

Lens: The clear lens provides maximum brightness and a sleek, modern look. The opal lens offers soft, diffused light and an elegant appearance.

Lamp: High power LEDs with 50,000 hrs. rated lamp life L70% lumen maintenance 3000K, 3500K, 4000K, 5000K color temperature CRI 80

Light distribution: Type V distribution

Driver: 60Hz, 120-277V / 347V / 480V electronic LED driver, thermally protected with low THD. 6kV native surge protection and 4kV EFT with ambient operating temperature -40°C to 55°C.

Options: tamperproof hardware, tamperproof bits, button photocell


Finish: black, white, silver grey, bronze, custom color available upon request, hydro-dipped

Listing: complies with CSA & UL standards; label for outdoor location


Warranty: 5-year limited warranty



UNB:





Front view



Top view

Anchoring Details:





CUSTOM ARCHITECTURAL LIGHTING

Toll free: 1 877 765 3722

• 120 Walker Dr, Brampton, ON L6T 4G9 CANADA

Fax: 905 457 1115

soleracorp.com

--	--	--	--	--	--	--	--	--	--

Name	Size	Light Engine	Electrical	Color Temp	Mounting	Lens	Light Pattern	Options	Finish
UNB	14 1/4"	42W	UNV	3000K	ABT	OPL	TY5	TP	BL
			347V	3500K		CL		TS	BZ
			480V	4000K				PC	WH
				5000K					SG
	custom wattage and size available								CC
									H-DIP

Notes:

- 3000K – 141 lm/w
- 3500K – 144 lm/w
- 4000K – 147 lm/w
- 5000K – 169 lm/w
- UNV – Universal voltage (120-277V)
- 347V – 347 volts
- 480V – 480 volts
- ABT – Anchors, bolts, & template
- OPL – Opal lens
- CL – Clear lens
- TY5 – Type V light distribution (std)
- TP – Tamperproof hardware
- TS – Tamperproof bits
- PC – Button photocell (voltage specific)
- BL – Minitex black
- BZ – Minitex bronze
- WH – Minitex white
- SG – Minitex silver grey
- CC – Custom color (confirm RAL No. prior to production)
- H-DIP – Hydro dipped finish (contact factory for pattern design options)